

DECLARATION OF PERFORMANCE - CE

CREOSOTE (PINE)

1. Unique identification code of the product-type: Wooden pole
2. Product identifier: Wooden pole
3. Intended use: Overhead line construction
4. Manufacturer: Burt Boulton & Haywood Ltd, Alexandra Docks, Newport, South Wales NP20 2WA, UNITED KINGDOM
email: sales@scanpole.com
5. AVCP system: AVCP 2+
6. DoP based on a harmonised product standard EN 14229:2010:
Notified body Finotrol Oy 2412 performed the initial inspection of the manufacturing plant and of its internal quality control and the continuous surveillance, assessment and approval and issued the certificate of conformity of the quality control No. 2412-CPR-1113
7. Declared performance:

Essential characteristics	Performance level	Harmonised technical specification
Wood species	PS: pine (pinus sylvestris)	BS EN 14229:2010 EN 14229:2010
Growth area	NNE Europe (Northern and North-Eastern Europe)	
Bending strength (MOR)	42,3 N/mm²	
Modulus of elasticity (MOE)	9718 N/mm²	
Release of dangerous substances	Timber treated with a biocides www.scanpole.com	
Durability, treated against biological attack		
Durability class	UC 4	
Retention	100 kg/m³	
Penetration class	NP 5	
Name of preservative	Creosote	

8. Signed for and on behalf of the manufacturer by

Joensuu 19.06.2025

Signature: Janne Monni

DECLARATION OF PERFORMANCE - CE

CREOSOTE (DOUGLAS FIR)

1. Unique identification code of the product-type: Wooden pole
2. Product identifier: Wooden pole
3. Intended use: Overhead line construction
4. Manufacturer: Burt Boulton & Haywood Ltd, Alexandra Docks, Newport, South Wales NP20 2WA, UNITED KINGDOM
email: sales@scanpole.com
5. AVCP system: AVCP 2+
6. DoP based on a harmonised product standard EN 14229:2010:
Notified body Finotrol Oy 2412 performed the initial inspection of the manufacturing plant and of its internal quality control and the continuous surveillance, assessment and approval and issued the certificate of conformity of the quality control No. 2412-CPR-1113
7. Declared performance:

Essential characteristics	Performance level	Harmonised technical specification
Wood species	PM: Coastal Douglas-Fir (pseudotsuga menziesii)	BS EN 14229:2010 EN 14229:2010
Growth area	CNE Europe (Central and North-Eastern Europe) Germany	
Bending strength (MOR)	34,1 N/mm² (mean BS EN 14229, EN 14229)	
Modulus of elasticity (MOE)	10 795 N/mm² (BS EN 14229, EN 14229)	
Release of dangerous substances	Timber treated with a biocides www.scanpole.com	
Durability, treated against biological attack		AWPA C4-03
Durability class	UC 4	
Retention	144 kg/m³	
Penetration class	19 mm (0,75 in) and 85 % of sapwood	
Name of preservative	Creosote	

8. Signed for and on behalf of the manufacturer by

Joensuu 19.06.2025

Signature: Janne Monni