

DECLARATION OF PERFORMANCE - CE

UNTREATED (PINE)

1. Unique identification code of the product-type: Wooden pole
2. Product identifier: Wooden pole
3. Intended use: Overhead line construction
4. Manufacturer: Scanpole Ltd, Alexandra Docks, Newport, South Wales NP20 2WA, UNITED KINGDOM  
email: sales@scanpole.com
5. AVCP system: AVCP 2+
6. DoP based on a harmonised product standard EN 14229:2010:  
Notified body Finotrol Oy 2412 performed the initial inspection of the manufacturing plant and of its internal quality control and the continuous surveillance, assessment and approval and issued the certificate of conformity of the quality control No. 2412-CPR-1118
7. Declared performance:

Essential characteristics	Performance level	Harmonised technical specification
Wood species	PS: pine (pinus sylvestris)	BS EN 14229:2010 EN 14229:2010
Growth area	NNE Europe (Northern and North-Eastern Europe)	
Bending strength (MOR)	42,3 N/mm²	
Modulus of elasticity (MOE)	9718 N/mm²	
Release of dangerous substances	NPD	
Non-treated against biological attack	3 - 4	BS EN 350:2016 EN 350:2016
Natural durability		

8. Signed for and on behalf of the manufacturer by

Joensuu 19.06.2025

Signature: Janne Monni

DECLARATION OF PERFORMANCE - CE

CREOSOTE (PINE)

1. Unique identification code of the product-type: Wooden pole
2. Product identifier: Wooden pole
3. Intended use: Overhead line construction
4. Manufacturer: Scanpole Ltd, Alexandra Docks, Newport, South Wales NP20 2WA, UNITED KINGDOM  
email: sales@scanpole.com
5. AVCP system: AVCP 2+
6. DoP based on a harmonised product standard EN 14229:2010:  
Notified body Finotrol Oy 2412 performed the initial inspection of the manufacturing plant and of its internal quality control and the continuous surveillance, assessment and approval and issued the certificate of conformity of the quality control No. 2412-CPR-1118
7. Declared performance:

Essential characteristics	Performance level	Harmonised technical specification
Wood species	PS: pine (pinus sylvestris)	BS EN 14229:2010 EN 14229:2010
Growth area	NNE Europe (Northern and North-Eastern Europe)	
Bending strength (MOR)	42,3 N/mm²	
Modulus of elasticity (MOE)	9718 N/mm²	
Release of dangerous substances	Timber treated with a biocides www.scanpole.com	
Durability, treated against biological attack		
Durability class	UC 4	
Retention	100 kg/m³	
Penetration class	NP 5	
Name of preservative	Creosote	

8. Signed for and on behalf of the manufacturer by

Joensuu 19.06.2025

Signature: Janne Monni

DECLARATION OF PERFORMANCE - CE

TANALITH E 3475 (PINE)

1. Unique identification code of the product-type: Wooden pole
2. Product identifier: Wooden pole
3. Intended use: Overhead line construction
4. Manufacturer: Scanpole Ltd, Alexandra Docks, Newport, South Wales NP20 2WA, UNITED KINGDOM  
email: sales@scanpole.com
5. AVCP system: AVCP 2+
6. DoP based on a harmonised product standard EN 14229:2010:  
Notified body Finotrol Oy 2412 performed the initial inspection of the manufacturing plant and of its internal quality control and the continuous surveillance, assessment and approval and issued the certificate of conformity of the quality control No. 2412-CPR-1118
7. Declared performance:

Essential characteristics	Performance level	Harmonised technical specification
Wood species	PS: pine (pinus sylvestris)	BS EN 14229:2010 EN 14229:2010
Growth area	NNE Europe (Northern and North-Eastern Europe)	
Bending strength (MOR)	42,3 N/mm²	
Modulus of elasticity (MOE)	9718 N/mm²	
Release of dangerous substances	Timber treated with a biocides www.scanpole.com	
Durability, treated against biological attack		
Durability class	UC 4	
Retention	20 kg/m³	
Penetration class	NP 5	
Name of preservative	Tanalith E 3475	

8. Signed for and on behalf of the manufacturer by

Joensuu 19.06.2025

Signature: Janne Monni

DECLARATION OF PERFORMANCE - CE

WOLMANIT CX-8 (PINE)

1. Unique identification code of the product-type: Wooden pole
2. Product identifier: Wooden pole
3. Intended use: Overhead line construction
4. Manufacturer: Scanpole Ltd, Alexandra Docks, Newport, South Wales NP20 2WA, UNITED KINGDOM  
email: sales@scanpole.com
5. AVCP system: AVCP 2+
6. DoP based on a harmonised product standard EN 14229:2010:  
Notified body Finotrol Oy 2412 performed the initial inspection of the manufacturing plant and of its internal quality control and the continuous surveillance, assessment and approval and issued the certificate of conformity of the quality control No. 2412-CPR-1118
7. Declared performance:

Essential characteristics	Performance level	Harmonised technical specification
Wood species	PS: pine (pinus sylvestris)	BS EN 14229:2010 EN 14229:2010
Growth area	NNE Europe (Northern and North-Eastern Europe)	
Bending strength (MOR)	42,3 N/mm²	
Modulus of elasticity (MOE)	9718 N/mm²	
Release of dangerous substances	Timber treated with a biocides www.scanpole.com	
Durability, treated against biological attack		
Durability class	UC 4	
Retention	18 kg/m³	
Penetration class	NP 5	
Name of preservative	Wolmanit CX-8	

8. Signed for and on behalf of the manufacturer by

Joensuu 19.06.2025

Signature: Janne Monni

## DECLARATION OF PERFORMANCE - CE

## TANASOTE S40 (PINE)

1. **Unique identification code of the product-type:** Wooden pole
2. **Product identifier:** Wooden pole
3. **Intended use:** Overhead line construction
4. **Manufacturer:** Scanpole Ltd, Alexandra Docks, Newport, South Wales NP20 2WA, UNITED KINGDOM  
email: sales@scanpole.com
5. **AVCP system:** AVCP 2+
6. DoP based on a harmonised product standard EN 14229:2010:  
Notified body Finotrol Oy 2412 performed the initial inspection of the manufacturing plant and of its internal quality control and the continuous surveillance, assessment and approval and issued the certificate of conformity of the quality control No. 2412-CPR-1118
7. **Declared performance:**

Essential characteristics	Performance level	Harmonised technical specification
Wood species	PS: pine (pinus sylvestris)	BS EN 14229:2010 EN 14229:2010
Growth area	NNE Europe (Northern and North-Eastern Europe)	
Bending strength (MOR)	42,3 N/mm <sup>2</sup>	
Modulus of elasticity (MOE)	9718 N/mm <sup>2</sup>	
Release of dangerous substances	Timber treated with a biocides www.scanpole.com	
Durability, treated against biological attack		
Durability class	UC 4	
Retention	85 kg/m <sup>3</sup>	
Penetration class	NP 5	
Name of preservative	Tanasote S40	

## 8. Signed for and on behalf of the manufacturer by

Joensuu 19.06.2025

Signature: Janne Monni

DECLARATION OF PERFORMANCE - CE

CREOSOTE (DOUGLAS FIR)

1. Unique identification code of the product-type: Wooden pole
2. Product identifier: Wooden pole
3. Intended use: Overhead line construction
4. Manufacturer: Scanpole Ltd, Alexandra Docks, Newport, South Wales NP20 2WA, UNITED KINGDOM  
email: sales@scanpole.com
5. AVCP system: AVCP 2+
6. DoP based on a harmonised product standard EN 14229:2010:  
Notified body Finotrol Oy 2412 performed the initial inspection of the manufacturing plant and of its internal quality control and the continuous surveillance, assessment and approval and issued the certificate of conformity of the quality control No. 2412-CPR-1118
7. Declared performance:

Essential characteristics	Performance level	Harmonised technical specification
Wood species	PM: Coastal Douglas-Fir (pseudotsuga menziesii)	BS EN 14229:2010 EN 14229:2010
Growth area	CNE Europe (Central and North-Eastern Europe) Germany	
Bending strength (MOR)	34,1 N/mm² (mean BS EN 14229, EN 14229)	
Modulus of elasticity (MOE)	10 795 N/mm² (BS EN 14229, EN 14229)	
Release of dangerous substances	Timber treated with a biocides www.scanpole.com	
Durability, treated against biological attack	UC 4  144 kg/m³  19 mm (0,75 in) and 85 % of sapwood  Creosote	AWPA C4-03
Durability class		
Retention		
Penetration class		
Name of preservative	Creosote	

8. Signed for and on behalf of the manufacturer by

Joensuu 19.06.2025

Signature: Janne Monni