

## DECLARATION OF PERFORMANCE - CE

# CREOSOTE (PINE)

- Unique identification code of the product-type:** Wooden pole
- Product identifier:** Wooden pole
- Intended use:** Overhead line construction
- Manufacturer:** Scanpole Ireland Ltd. Oldmilltown, Kill, Co. Kildare. W91 FY96, IRELAND  
email: sales@scanpole.com
- AVCP system:** AVCP 2+
- DoP based on a harmonised product standard EN 14229:2010:**  
**Control Union Finland**, Notified Body (2412), performed the initial inspection of the manufacturing plant and of its internal quality control and the continuous surveillance, assessment and approval and issued the certificate of conformity of the quality control No. 2412-CPR-1120
- Declared performance:**

Essential characteristics	Performance level	Harmonised technical specification
Wood species	PS: pine (pinus sylvestris)	BS EN 14229:2010 EN 14229:2010
Growth area	NNE Europe (Northern and North-Eastern Europe)	
Characteristic bending strength (MOR)	42,3 N/mm <sup>2</sup>	
Characteristic modulus of elasticity (MOE)	9718 N/mm <sup>2</sup>	
Release of dangerous substances	Timber treated with a biocides <a href="http://www.scanpole.com">www.scanpole.com</a>	
Durability, treated against biological attack		
Durability class	UC 4	
Retention	100 kg/m <sup>3</sup>	
Penetration class	NP 5	
Name of preservative	Creosote	

### 8. Signed for and on behalf of the manufacturer by

Joensuu 1.3.2026

Signature: Janne Monni  
CEO, Scanpole Group

**DECLARATION OF PERFORMANCE - CE**

**CREOSOTE (DOUGLAS FIR)**

- 1. **Unique identification code of the product-type:** Wooden pole
- 2. **Product identifier:** Wooden pole
- 3. **Intended use:** Overhead line construction
- 4. **Manufacturer:** Scanpole Ireland Ltd. Oldmilltown, Kill, Co. Kildare. W91 FY96, IRELAND  
email: sales@scanpole.com
- 5. **AVCP system:** AVCP 2+
- 6. **DoP based on a harmonised product standard EN 14229:2010:**  
**Control Union Finland**, Notified Body (2412), performed the initial inspection of the manufacturing plant and of its internal quality control and the continuous surveillance, assessment and approval and issued the certificate of conformity of the quality control No. 2412-CPR-1120
- 7. **Declared performance:**

Essential characteristics	Performance level	Harmonised technical specification
Wood species	Coastal Douglas-Fir (pseudotsuga menziesii)	BS EN 14229:2010 EN 14229:2010
Growth area	Europe and North America	
Characteristic bending strength (MOR)	34,6N/mm <sup>2</sup>	
Characteristic modulus of elasticity (MOE)	11 541 N/mm <sup>2</sup>	
Release of dangerous substances	Timber treated with a biocides www.scanpole.com	
Durability, treated against biological attack		AWPA C4-03
Durability class	UC 4	
Retention	144 kg/m <sup>3</sup>	
Penetration class	19 mm (0,75 in) and 85 % of sapwood	
Name of preservative	Creosote	

**8. Signed for and on behalf of the manufacturer by**

Joensuu 1.3.2026

Signature: Janne Monni  
CEO, Scanpole Group

**DECLARATION OF PERFORMANCE - CE**

**TANASOTE S40 (DOUGLAS FIR)**

- 1. **Unique identification code of the product-type:** Wooden pole
- 2. **Product identifier:** Wooden pole
- 3. **Intended use:** Overhead line construction
- 4. **Manufacturer:** Scanpole Ireland Ltd. Oldmilltown, Kill, Co. Kildare. W91 FY96, IRELAND  
email: sales@scanpole.com
- 5. **AVCP system:** AVCP 2+
- 6. **DoP based on a harmonised product standard EN 14229:2010:**  
**Control Union Finland**, Notified Body (2412), performed the initial inspection of the manufacturing plant and of its internal quality control and the continuous surveillance, assessment and approval and issued the certificate of conformity of the quality control No. 2412-CPR-1120

7. **Declared performance:**

Essential characteristics	Performance level	Harmonised technical specification
Wood species	PM: Coastal Douglas-Fir (pseudotsuga menziesii)	BS EN 14229:2010 EN 14229:2010
Growth area	Europe and North America	
Characteristic bending strength (MOR)	34,6 N/mm <sup>2</sup>	
Characteristic modulus of elasticity (MOE)	11 541 N/mm <sup>2</sup>	
Release of dangerous substances	Timber treated with a biocides www.scanpole.com	
Durability, treated against biological attack		
Durability class	UC 4	AWPA C4-03
Retention	86,5 kg/m <sup>3</sup>	
Penetration class	19 mm (0,75 in) and 85 % of sapwood	
Name of preservative	Tanasote S40	

8. **Signed for and on behalf of the manufacturer by**

Joensuu 1.3.2026

Signature: Janne Monni  
CEO, Scanpole Group

**DECLARATION OF PERFORMANCE - CE**

**CREOSOTE (SOUTHERN YELLOW PINE)**

1. **Unique identification code of the product-type:** Wooden pole
2. **Product identifier:** Wooden pole
3. **Intended use:** Overhead line construction
4. **Manufacturer:** Scanpole Ireland Ltd. Oldmilltown, Kill, Co. Kildare. W91 FY96, IRELAND  
email: sales@scanpole.com
5. **AVCP system:** AVCP 2+
6. **DoP based on a harmonised product standard EN 14229:2010:**  
**Control Union Finland**, Notified Body (2412), performed the initial inspection of the manufacturing plant and of its internal quality control and the continuous surveillance, assessment and approval and issued the certificate of conformity of the quality control No. 2412-CPR-1120
7. **Declared performance:**

Essential characteristics	Performance level	Harmonised technical specification
Wood species	Southern Yellow Pine	BS EN 14229:2010 EN 14229:2010
Growth area	Georgia, United States	
Characteristic bending strength (MOR)	43,3 N/mm <sup>2</sup>	
Characteristic modulus of elasticity (MOE)	10 519 N/mm <sup>2</sup>	
Release of dangerous substances	Timber treated with a biocides www.scanpole.com	
Durability, treated against biological attack		AWPA C4-03
Durability class	UC 4	
Retention	144 kg/m <sup>3</sup>	
Penetration class	90 % of sapwood	
Name of preservative	Creosote	

**8. Signed for and on behalf of the manufacturer by**

Joensuu 1.3.2026

Signature: Janne Monni  
CEO, Scanpole Group

**DECLARATION OF PERFORMANCE - CE**

**TANASOTE S40 (SOUTHERN YELLOW PINE)**

- 1. **Unique identification code of the product-type:** Wooden pole
- 2. **Product identifier:** Wooden pole
- 3. **Intended use:** Overhead line construction
- 4. **Manufacturer:** Scanpole Ireland Ltd. Oldmilltown, Kill, Co. Kildare. W91 FY96, IRELAND  
email: sales@scanpole.com
- 5. **AVCP system:** AVCP 2+
- 6. **DoP based on a harmonised product standard EN 14229:2010:**  
**Control Union Finland**, Notified Body (2412), performed the initial inspection of the manufacturing plant and of its internal quality control and the continuous surveillance, assessment and approval and issued the certificate of conformity of the quality control No. 2412-CPR-1120
- 7. **Declared performance:**

Essential characteristics	Performance level	Harmonised technical specification
Wood species	Southern Yellow Pine	BS EN 14229:2010 EN 14229:2010
Growth area	Georgia, United States	
Characteristic bending strength (MOR)	43,3 N/mm <sup>2</sup>	
Characteristic modulus of elasticity (MOE)	10 519 N/mm <sup>2</sup>	
Release of dangerous substances	Timber treated with a biocides www.scanpole.com	
Durability, treated against biological attack		
Durability class	UC 4	AWPA C4-03
Retention	86,5 kg/m <sup>3</sup>	
Penetration class	90 % of sapwood	
Name of preservative	Tanasote S40	

**8. Signed for and on behalf of the manufacturer by**

Joensuu 1.3.2026

Signature: Janne Monni  
CEO, Scanpole Group

## DECLARATION OF PERFORMANCE - CE

# TANASOTE S40 (PINE)

- Unique identification code of the product-type:** Wooden pole
- Product identifier:** Wooden pole
- Intended use:** Overhead line construction
- Manufacturer:** Scanpole Ireland Ltd. Oldmilltown, Kill, Co. Kildare. W91 FY96, IRELAND  
email: sales@scanpole.com
- AVCP system:** AVCP 2+
- DoP based on a harmonised product standard EN 14229:2010:**  
**Control Union Finland**, Notified Body (2412), performed the initial inspection of the manufacturing plant and of its internal quality control and the continuous surveillance, assessment and approval and issued the certificate of conformity of the quality control No. 2412-CPR-1120
- Declared performance:**

Essential characteristics	Performance level	Harmonised technical specification
Wood species	PS: pine (pinus sylvestris)	BS EN 14229:2010 EN 14229:2010
Growth area	NNE Europe (Northern and North-Eastern Europe)	
Characteristic bending strength (MOR)	42,3 N/mm <sup>2</sup>	
Characteristic modulus of elasticity (MOE)	9718 N/mm <sup>2</sup>	
Release of dangerous substances	Timber treated with a biocides <a href="http://www.scanpole.com">www.scanpole.com</a>	
Durability, treated against biological attack		
Durability class	UC 4	
Retention	86,5 kg/m <sup>3</sup>	
Penetration class	NP 5	
Name of preservative	Tanasote S40	

### 8. Signed for and on behalf of the manufacturer by

Joensuu 1.3.2026

Signature: Janne Monni  
CEO, Scanpole Group

**DECLARATION OF PERFORMANCE - CE**

**TANALITH E3475 (PINE)**

- 1. **Unique identification code of the product-type:** Wooden pole
- 2. **Product identifier:** Wooden pole
- 3. **Intended use:** Overhead line construction
- 4. **Manufacturer:** Scanpole Ireland Ltd. Oldmilltown, Kill, Co. Kildare. W91 FY96, IRELAND  
email: sales@scanpole.com
- 5. **AVCP system:** AVCP 2+
- 6. **DoP based on a harmonised product standard EN 14229:2010:**  
**Control Union Finland**, Notified Body (2412), performed the initial inspection of the manufacturing plant and of its internal quality control and the continuous surveillance, assessment and approval and issued the certificate of conformity of the quality control No. 2412-CPR-1120
- 7. **Declared performance:**

Essential characteristics	Performance level	Harmonised technical specification
Wood species	PS: pine (pinus sylvestris)	BS EN 14229:2010 EN 14229:2010
Growth area	NNE Europe (Northern and North-Eastern Europe)	
Characteristic bending strength (MOR)	42,3 N/mm <sup>2</sup>	
Characteristic modulus of elasticity (MOE)	9718 N/mm <sup>2</sup>	
Release of dangerous substances	Timber treated with a biocides www.scanpole.com	
Durability, treated against biological attack		
Durability class	UC 4	
Retention	20 kg/m <sup>3</sup>	
Penetration class	NP 5	
Name of preservative	Tanalith E3475	

**8. Signed for and on behalf of the manufacturer by**

Joensuu 1.3.2026

Signature: Janne Monni  
CEO, Scanpole Group